


Normalization of dialects and variants using FST technology

Rules in foma


Iñaki Alegria
(University of The Basque Country)

Languages: finite automata


“one or more as”: $\{a, aa, \dots\}$:



the words “cat” and “dog”:



any word that contains at least an a:




@ = any symbol outside the defined alphabet

Finite transducers

Translates all a-symbols to b and vice versa




Translates “cat” to “katua”



Devoice end-of-word stops:
xleb \rightarrow xlep, rad \rightarrow rat, etc.

*Convention: a single symbol on an arc (a) is shorthand for an identity pair (a:a)





Birds-eye view

Rule-based normalization tends to model changes from variants to standard/pivot/canonical forms writing rules, which are based on regular expressions and compiled into transducers

variants → standard forms

With this aim, basically phonological changes will be described (but lemmas, affixes, stems and other morphological elements can be interesting)

phoneme → phoneme

morph-element → morph-element

Each change/rule is compiled into a transducer and the transducers can be composed all together



Using *foma*

- Unix-like commands
- A general-purpose tool for constructing and manipulating automata and transducers
- Contains a regular expression compiler to convert expressions (including “rewrite rules”) to transducers
- Contains a lexc-parser to construct transducers from lexicon descriptions (no for today)
- API available (in C) for integration with other programs
- [source & binaries for Linux, Mac, and Windows]



foma: hands-on

Compiling regular expressions: regex

```
regex a+;
```

```
regex c a t | d o g;
```

```
regex ?* a ?*;
```

```
regex [a:b | b:a]*;
```

```
regex [c a t]:[k a t u a];
```

```
regex b -> p , g -> k, d -> t || _ .#.;
```

[demo]



foma: hands-on

(space) concatenation

| union

* Kleene star

& Intersection

~ Complement

foma: ordinary symbols

Single-character symbols:


a, b, c, Ω, ب, β, etc.

Multi-character symbols:

[Noun], +3pSg, @a_symbol@, cat, dog


foma[0]: **regex cat**;

168 bytes. 2 states, 1 arcs, 1 path.



foma[1]: **regex c a t**;

257 bytes. 4 states, 3 arcs, 1 path.





foma: special symbols

- 0 the empty string (epsilon)
- ? “any” symbol (similar to . in grep/perl/awk/sed-regexes, or Σ in “formal language” regexes)



foma: contd.

testing automata against words:

foma[0]: **regex** **?* a ?***;

261 bytes. 2 states, 4 arcs, Cyclic.

foma[1]: down

apply down> **ab**

ab

apply down> **xax**

xax

apply down> **bbx**

???

apply down> **^D**

foma[1]:



foma: contd.

running transducers:

foma[0]: **regex [c a t]:[k a t u a];**
317 bytes. 6 states, 5 arcs, 1 path.

foma[1]: **down**

apply down> **cat**

katua

apply down> **dog**

???

foma[1]: **up**

apply up> **katua**

cat



Examining FSMs

foma[0]: **regex** **?* a ?***;

261 bytes. 2 states, 4 arcs, Cyclic.

foma[1]: **net**

Sigma: @ a

Size: 1.

Net: 41A7

Flags: deterministic pruned minimized epsilon_free

Arity: 1

Ss0: @ -> s0, a -> fs1.

fs1: @ -> fs1, a -> fs1.

foma[1]:


Examining FSMs visually

foma[0]: **regex $?^* a ?^*$** ;

261 bytes. 2 states, 4 arcs, Cyclic.

foma[1]: view

foma[1]:





More about foma

Labeling FSMs: the define command

```
foma[0]: define V [a|e|i|o|u];
```

defined V: 317 bytes. 2 states, 5 arcs, 5 paths.

```
foma[0]: define StartsWithVowel [V ?*];
```

defined StartsWithVowel: 429 bytes. 2 states, 11 arcs,
Cyclic.

```
foma[0]:
```



Define contd.

foma[0]: **define V [a|e|i|o|u];**

redefined V: 317 bytes. 2 states, 5 arcs, 5 paths.

foma[0]: **define C [b|d|g|k|m|n|p|s|t|v|z];**

defined C: 497 bytes. 2 states, 11 arcs, 11 paths.

foma[0]: **define Syllable [C* V+ C*];**

defined Syllable: 1.0 kB. 3 states, 43 arcs, Cyclic.

foma[0]: **define PhonologicalWord Syllable+;**

defined PhonologicalWord: 887 bytes. 2 states, 32 arcs, Cyclic.

foma[0]: **print defined**

V 317 bytes. 2 states, 5 arcs, 5 paths.

StartsWithVowel 429 bytes. 2 states, 11 arcs, Cyclic.

C 497 bytes. 2 states, 11 arcs, 11 paths.

Syllable 1.0 kB. 3 states, 43 arcs, Cyclic.

PhonologicalWord 887 bytes. 2 states, 32 arcs, Cyclic.



Transducer operations

Composition (operator: **.o.**)

```
foma[0]: define EngBasque [c a t]:[k a t u a];  
defined EngBasque: 317 bytes. 6 states, 5 arcs, 1 path.  
foma[0]: define BasqueFinn [k a t u a]:[k i s s a];  
defined BasqueFinn: 331 bytes. 6 states, 5 arcs, 1 path.  
foma[0]: regex EngBasque .o. BasqueFinn;  
345 bytes. 6 states, 5 arcs, 1 path.  
foma[1]: down  
apply down> cat  
kissa  
apply down>
```




Replacement rules

Simple replacement:

foma[0]: **regex a -> b ;**

290 bytes. 1 states, 3 arcs, Cyclic.

foma[1]: **down**

apply down> **a**

b

apply down> **axa**

bxb

apply down>



Replacement rules

Conditional replacement

foma[0]: **regex a -> b || c _ d;**

526 bytes. 4 states, 16 arcs, Cyclic.

foma[1]: down

apply down> **cadca**

cbdca

apply down>



Replacement rules

Conditional replacement w/ multiple contexts.

foma[0]: **regex a -> b || c _ d , e _ f;**

890 bytes. 7 states, 37 arcs, Cyclic.

foma[1]: down

apply down> **cadeaf**

cbdebf

apply down> **a**

a

apply down>



Replacement rules

“Parallel” rules, the .#.-symbol

Example: devoice some word-final stops

```
foma[0]: regex b -> p , g -> k , d -> t || _ .# . ;
```

634 bytes. 3 states, 20 arcs, Cyclic.

```
foma[1]: down
```

```
apply down> cab
```

```
cap
```

```
apply down> dog
```

```
dok
```

```
apply down> dad
```

```
dat
```



Replacement rules & composition

We can define multiple different rules and compose them into one single transducer:

```
foma[0]: define Rule1 a -> b || c _ ;  
defined Rule1: 384 bytes. 2 states, 8 arcs, Cyclic.  
foma[0]: define Rule2 b -> c || _ d;  
defined Rule2: 416 bytes. 3 states, 10 arcs, Cyclic.  
foma[0]: regex Rule1 .o. Rule2;  
574 bytes. 4 states, 19 arcs, Cyclic.  
foma[1]: down  
apply down> cad  
ccd  
apply down> ca  
cb  
apply down> ad  
ad
```



Optional replacement

Simple optional replacement:

foma[0]: regex a (->) b ;

290 bytes. 1 states, 3 arcs, Cyclic.

foma[1]: down

apply down> a

a

b

apply down> axa

axa

axb

bxa

bxb



Review of basic *foma* regexes

Special symbols \emptyset (epsilon) and ϵ (the “any” symbol)

[and] are grouping symbols

_ is a context separator (don't use in definitions)

$\cdot\#$ is a special symbol indicating left or right word boundary in replacement rules

Reserved symbols (operators) need to be quoted if used as symbols: eg. a “ $\&$ ” b;

space	concatenation	:	Cross-product
	union	$A \rightarrow B$	Replacement rules
*	Kleene star	$A (-\rightarrow) B$	Opt. replacement
+	Kleene plus	$A \rightarrow B \parallel C _ D$	Context-conditioned
&	Intersection	$A (-\rightarrow) B \parallel C _ D$	
~	Complement	$\cdot\mathbf{o}\cdot$	Composition
(A)	Optionality (identical to $A \mid \emptyset$)		



Review of basic *foma* commands

Compile regex:

```
regex regular-expression;
```

Name a FST/FSM using a regex:

```
define name regular-expression;
```

View (visually) a compiled regex:

```
view or view net
```

Run a word through a transducer:

```
down <word> or apply down <word>
```

In the inverse direction:

```
up <word> or apply up <word>
```

Print all the words an automaton accepts:

```
words or print words
```

Only lower/upper side words (for a transducer):

```
lower-words or print lower-words
```

```
upper-words or print upper-words
```

Load word-lists:

```
read txt name.txt
```

Save binary (for including or for using flookup in test-scripts):

```
save stack name.fst
```




foma and flookup

First steps using REs:

```
foma
```

Writing, compiling and testing grammars:

```
gedit grammar.txt &  
foma -l grammar.txt
```

Scripting (test):

```
flookup grammar.fst # equivalent to apply up  
flookup -i          # equivalent to apply down  
flookup -h          # list options  
flookup -ibx        # inverse, no buffer, no echo
```